

CAPP Aero384

MULTICHANNEL PIPETTES

CAPP Aero384 Multichannel Pipettes For 384-well Plates

Most applications involving 384-well plates are performed using automated systems.

CAPP provides the world's only alternative for the quick and high precision pipetting of 16-, 48-, or 64-wells at once without the use of expensive, automated equipment.

Ideal For 384-well Liquid Handling

The **CAPP Aero384** 48 & 64 channel pipette allows for pipetting large samples within a short period of time while reducing the workload.

The **CAPP Aero384** is generally applicable for all transfers of liquids from reservoir and 384 deep-well plates into 384 well test plates, and it offers very obvious advantages in PCR, micro array, and MALDI spectrometry techniques.

CAPP Aero384 Multichannel Pipettes feature lightweight construction and produce a consistent and reliable liquid transfer result in one ergonomic solution.

EXPellPlus384™ Low Retention Tips

High quality, low retention tips

CAPP offers a range of **EXPellPlus384™** tips which are specifically designed to perfectly fit the **CAPP** range of 384 well pipetting. Due to special polymers and an extremely smooth inside surface, the **EXPellPlus384™** tips from **CAPP** virtually eliminate sample retention, and reduce the binding of DNA, RNA, and Proteins to a minimum.

The range also includes a filter tip version to effectively prevent cross contamination due to aerosol formation (such as DNA), and dangers from toxic, infectious, radioactive or other hazardous material's carry over.



Ordering Information

Cat. No.	Description	Inaccuracy %	Imprecision %	Colour
650540	CAPP multi pipettes, 16-channel, 0.2-2 μ L	4.00	2.00	●
650541	CAPP multi pipettes, 16-channel, 0.5-10 μ L	2.00	1.00	○
650542	CAPP multi pipettes, 16-channel, 5-50 μ L	1.40	0.60	●
650545	CAPP multi pipettes, 48-channel, 0.5-10 μ L	4.00	2.00	○
650547	CAPP multi pipettes, 64-channel, 0.5-10 μ L	4.00	2.00	○

EXPellPlus 384 Low Retention Tips

Cat. No.	Description	Qty/pack	Packs/case
670500	ExpellPlus 0.2-50 μ L, racked, sterile	10 x 384	5
670501	ExpellPlus 0.2-50 μ L, racked, sterile, filtered 10 x 384		5