



BenchRocker™ 2D Variable Speed Rocker (2D)



- + Adjustable tilt & speed for a wide range of applications
- + Large 35 x 30 cm work surface
- + Safe for incubator or cold room use

The BenchRocker 2D is designed to provide the precise speeds and tilt angles required for a broad range of molecular and biological mixing applications. The user can adjust both parameters to match the vessel size and the volume of liquid being mixed, yielding optimum results.

Technical Data:

Speed Range:	Variable, 2 to 30 rpm
Tilt Angle:	Variable, 0° to ± 30°
Platform Size:	35 x 30 cm
Load Capacity:	3.6 kg
Operating Temp. Range:	+4 °C to +45 °C
Dimensions: (W x D x H)	35 x 30 x 20 cm
Stacking Clearance:	7.6 cm
Weight:	3.4 kg
Electrical:	230V, 50-60Hz, 50W
Warranty:	2 Years

Ordering Information:

Item No.	Description:
55BR2000-E	BenchRocker™ 2D Rocker with flat mat
55BR2000-STACK	Optional stacking platform (7.6 cm) with flat mat
55BR1000-DIMPLED	Optional dimpled mat
55B0718	Bungee cord, used for securing vessels, pack of 4
55BR2000-SP	STACK-PLUS Extender set, adds 3,2 cm clearance to stacking platform



Everlast™ 247 Heavy Duty - Variable Speed Rocker (2D)



- + Everlast™ 5 year warranty
- + Extra-large, stainless steel 41 x 31 cm surface
- + 5.4 kg load capacity
- + Safe for incubator or cold room use

With an unprecedented 5 year limited warranty, Benchmark's Everlast 247 Rocker is built to last. Twenty four hours a day, seven days a week . . . No problem!
The powerful motor and heavy duty drive system remain reliable and consistent, even under constant usage in a cold room (min. 0 °C) or incubator (max. 65 °C).

Technical Data:

Speed Range:	Variable, 3 to 80 rpm
Tilt Angle:	Variable, 0° to ± 20°
Platform Size:	40.5 x 30 cm
Load Capacity:	5.45 kg
Operating Temp. Range:	+0 °C to +65 °C
Dimensions: (W x D x H)	40.5 x 33 x 15.25 cm
Stacking Clearance:	8.9 cm
Weight:	9 kg
Electrical:	230V, 50-60Hz, 50W
Warranty:	5 Years

Ordering Information:

Item No.	Description:
55BR5000-E	Everlast™ 247 Rocker with flat mat
55BR5000-STACK	Optional stacking platform with flat mat with 8.9 cm clearance
55B0718	Bungee cord, used for securing vessels, pack of 4